CALIBRATION TESTER

I CAL - 25



Designed to calibrate measuring accuracy of Indicators and Comparators



Compliance with ABBE principle

Integrated with 25mm stroke USB Electronic Gauge Head

Direct Connect with PC without interface assistance

Flexible & easy to use due to wide range of accessories

Specification:

Measuring Range	25mm
Resolution	0.0001mm
Repeatability	0.0002mm
Accuracy (at 20° C)	0.0015mm
Read Out	Software
PC Interface	USB
Operation	Manual
Size (LxWxH)	150x200x600mm
Weight	15 kg
Power Input	230 VAC, 50Hz



Accessories:



Application for Plunger Type Indicator Accessory

Can clamp Indicators and Probes with shank diameter 8mm



Application for
Dial Test
Indicator Accessory

Can clamp Indicator stems with multi diameters 4mm, 8mm and 9.5mm



Application for Bore Gauge
Accessories Set

Can clamp Bore Gauges (single point) of larger ranges up to 400mm



Application for Read Out Software

- Windows 10 Compatible
- Data export to Excel
- Error Compensation Facility
- Pre-Set Facility
- Min / Max Options
- Mm / inch selectable



Application for Calibration Software

- Windows 10 Compatible
- Calibration program compliance with IS and JIS Standards
- Calibration certificate format compliance with ISO/IEC17025 Standard Customization of Certificate format - as optional

Contact

Metric Measurement Technologies